

Gauges for Pneumatics

Product Number	Description
14004904-001	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (-40 to 160 F), +/- 2% accuracy. Replaces 14506495-001(gauge) + 14505846-001
14004904-002	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (0 to 200 F), +/- 2% accuracy. Replaces 4506495-001(gauge) + 14505846-002
14004904-003	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (40 to 240 F), +/- 2% accuracy, Replaces 14506495-001(gauge) + 14505846-003
14004904-004	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (3 to 15 psi), +/- 2% accuracy, Replaces 14506495-001(gauge) + 14505846-022
14004904-005	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (0 to 20 psi), +/- 2% accuracy, Replaces 14506495-001(gauge) + 14505846-023
14004904-006	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (25 to 125 F), +/- 2% accuracy, Replaces 14506495-001(gauge) + 14505846-004
14004904-007	2-1/2 in. diameter, panel mount Pneumatic Receiver gauge (50 to 100 F), +/- 2% accuracy, Replaces 14506495-001(gauge) + 14505846-005,
14004904-008	2-1/2 in. diameter, Pneumatic Receiver gauge (-20 to 80 F), +/- 2% accuracy
14004904-009	2-1/2 in. diameter, Pneumatic Receiver gauge (0 to 2 in. wc), +/- 2% accuracy
14004904-010	2-1/2 in. diameter, Pneumatic Receiver gauge (15 to 85% RH), +/- 2% accuracy
14004904-011	2-1/2 in. diameter, Pneumatic Receiver gauge (15 to 75% RH), +/- 2% accuracy
14004904-012	2-1/2 in. diameter, Pneumatic Receiver gauge (15 to 95% RH), +/- 2% accuracy
14004904-101	2-1/2 in. diameter, Pneumatic Receiver gauge (-40 to 160 F), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-001
14004904-102	2-1/2 in. diameter, Pneumatic Receiver gauge (0 to 200 F), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-002
14004904-103	2-1/2 in. diameter, Pneumatic Receiver gauge (40 to 240 F), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-003
14004904-104	2-1/2 in. diameter, Pneumatic Receiver gauge (3 to 15 psi), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-022
14004904-105	2-1/2 in. diameter, Pneumatic Receiver gauge (0 to 20 psi), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-023
14004904-106	2-1/2 in. diameter, Pneumatic Receiver gauge (25 to 125 F), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-004
14004904-107	2-1/2 in. diameter, Pneumatic Receiver gauge (50 to 100 F), +/- 1% accuracy. Replaces 14506495-101(gauge) + 14505846-005
14004905-001	3-1/2 in. diameter, Pneumatic Receiver gauge (-40 to 160 F), +/- 2% accuracy
14004905-002	3-1/2 in. diameter, Pneumatic Receiver gauge (0 to 200 F), +/- 2% accuracy. Replaces 14506496-001(gauge) + 14505846-102
14004905-003	3-1/2 in. diameter, Pneumatic Receiver gauge (40 to 240 F), +/- 2% accuracy. Replaces 14506496-001(gauge) + 14505846-103
14004905-004	3-1/2 in. diameter, Pneumatic Receiver gauge (3 to 15 psi), +/- 2% accuracy. Replaces 14506496-001(gauge) + 14505846-122
14004905-005	3-1/2 in. diameter, Pneumatic Receiver gauge (0 to 20 psi), +/- 2% accuracy. Replaces 14506496-001(gauge) + 14505846-123
14004905-006	3-1/2 in. diameter, Pneumatic Receiver gauge (25 to 125 F), +/- 2% accuracy. Replaces 14506496-001(gauge) + 14505846-104
14004905-007	3-1/2 in. diameter, Pneumatic Receiver gauge (50 to 100 F), +/- 2% accuracy. Replaces 14506496-001(gauge) + 14505846-105
14004905-008	3-1/2 in. diameter, Pneumatic Receiver gauge (-20 to 80 F), +/- 2% accuracy
14004905-009	3-1/2 in. diameter, Pneumatic Receiver gauge (0 to 2 in. wc), +/- 2% accuracy
14004905-010	3-1/2 in. diameter, Pneumatic Receiver gauge (15 to 85% RH), +/- 2% accuracy
14004905-011	3-1/2 in. diameter, Pneumatic Receiver gauge (15 to 75% RH), +/- 2% accuracy
14004905-012	3-1/2 in. diameter Pneumatic Receiver gauge (15 to 95% RH), +/- 2% accuracy
14004905-101	3-1/2 in. diameter, Pneumatic Receiver gauge (-40 to 160 F), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-101
14004905-102	3-1/2 in. diameter, Pneumatic Receiver gauge (0 to 200 F), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-102
14004905-103	3-1/2 in. diameter, Pneumatic Receiver gauge (40 to 240 F), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-103
14004905-104	3-1/2 in. diameter, Pneumatic Receiver gauge (3 to 15 psi), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-122
14004905-105	3-1/2 in. diameter, Pneumatic Receiver gauge (0 to 20 psi), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-123
14004905-106	3-1/2 in. diameter, Pneumatic Receiver gauge (25 to 125 F), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-104
14004905-107	3-1/2 in. diameter, Pneumatic Receiver gauge (50 to 100 F), +/- 1% accuracy. Replaces 14506496-101(gauge) + 14505846-105
305616	1-1/2 in. diameter, 1/8 NPT center stem back mount Receiver gauge (0 to 2 in. wc scale) with +/- 2% accuracy

Gauges and Accessories

Product Number	Description
305617	1-1/2 in. diameter, 1/8 NPT center stem back mount Receiver gauge (1.0 to 3.0 in. wc scale) with +/- 2% accuracy
305911	Gauge, 2 in., 0-160PSI, 1/8 in. NPT
305912	Gauge, 0-100PSI, 2 in., 1/8 in. NPT
305914	2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 3% accuracy
305917	2 in. diameter, 1/4 NPT center stem back mount Pressure Indicating gauge (0 to 160 psi scale) with +/- 3% accuracy
305923	1-1/2 in. diameter, 1/8 NPT stem on bottom mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy
305925	Gauge, 0-30 PSI, 2 in., 1/8 in. NPT
305929	1-1/2 in. diameter, 1/8 NPT center back stem mount Receiver gauge (-40 to +160 F scale) with +/- 2% accuracy
305930	1-1/2 in. diameter, 1/8 NPT center back stem mount Receiver gauge (0 to 200 F scale) with +/- 2% accuracy
305931	1-1/2 in. diameter, 1/8 NPT center back stem mount Receiver gauge (40 to 240 F scale) with +/- 2% accuracy
305935	3-1/2 in. diameter, surface mounted 1/8 NPT stem on bottom Receiver gauge (-40 to +160 F scale) with +/- 2% accuracy
305965	1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy
305986	Receiver Gauge. -20 to 80 F scale 1-1/2 in. diameter, 1/2 NPT connection
305989	Gauge, Dew Point, 5-25C, 1.5 in., 1/8 in. NPT
804190C	3-1/2 in. diameter, panel-mounted Pneumatic Pressure Indicating Gauge (0 to 60 psi), 1/8 in. NPT connection, +/-3% accuracy
804191B	2-1/2 in. diameter, panel-mounted Pneumatic Pressure Indicating Gauge (0 to 30 psi), 1/4 in. barbed connection, +/-3% accuracy
804191C	2-1/2 in. diameter, panel-mounted Pneumatic Pressure Indicating Gauge (0 to 60 psi), 1/8 in. NPT connection, +/-3% accuracy
804191E	2-1/2 in. diameter, panel-mounted Pneumatic Pressure Indicating Gauge (0 to 160 psi), 1/8 in. NPT connection, +/-3% accuracy

Pneumatic Accessories

Product Number	Description	Used With
14002913-002	External Restriction Assembly. 0.007 in. Restriction, Red, Inlet 1/4 in; Outlet 1/4 in. and 1/4 in.	LP907; RP9517
14002913-003	External Restriction Assembly. 0.007 in. Restriction, Red, Inlet 1/4 in; Outlet 1/4 in. and 5/32 in.	LP907
14002913-004	External Restriction Assembly. 0.005 in. Restriction, Blue Inlet 1/4 in; Outlet 5/32 in. and 5/32 in.	—
14002913-005	External Restriction Assembly. 0.007 in. Restriction, Blue Inlet 1/4 in; Outlet 5/32 in. and 5/32 in.	—
14002913-007	External Restriction Assembly. 0.013 in. Restriction, Gray and Red, Inlet 1/4 in; Outlet 1/4 in. and 1/4 in.	—
14002914-001	Internal Restriction Assembly, 0.005 in. Restriction, Blue	RP975; SP970
14002914-002	Internal Restriction Assembly, 0.013 in. Restriction, Gray	—
14002914-004	Internal Restriction Assembly, 0.008 in. Restriction, Red	—
14003078-004	Three position switch, same as SP470A1018 without the scaleplate	SP470A1018
14003428-001	Amber tint filter bowl 4 1/64 inch long x 2 59/64 inch diameter including Bushing (313003)	WP251A
14003519-001	0-30 psi Gauge Kit with Fittings for Copper or Poly Tubing	—
14003567-001	Cap-barb with linear of low density polyethylene	14002913
14004239-001	Total air flow pick-up Tube assembly	PP904A
14004441-003	Bag assembly, with Spring [silver] (14001992-001) window [vertical. Logo] (14004405-001), window [horizontal. Logo] (14004405-002), window [vertical. 60-90] (14004405-005), 1 window [horizontal. 60-90] (14004405-014)	—
14004441-015	Bag assembly with window [vertical. Logo], window [horizontal. Logo], window [vertical. 60-90], window [horizontal 60-90], Cover insert, setpoint, and window [vertical. 60-90]	—
14004559-001	Connector bag assembly, with connector assembly and connector assembly	Pneumatic Fittings
14004596-004	1 1/4 in. Bonnet for V5011/V5013	V5011; V5013
14004695-002	Pneumatic indicator - 1 7/8 in. +/- 1/16 in. X 5/8 in. +/- 1/32 in. Red =energized color, black de-energized color	—
14501547-001	ISD Central relay panel	—

Gauges and Accessories

Product Number	Description	Used With
14501600-001	Resistor Assembly PPK, End of Line Resistor, 1.91K Ohms Single Zone Fire Alarm Panels	—
14501600-002	Resistor Assembly PPK, End of Line Resistor, 1.91K Ohms Single Zone Fire Alarm Panels	—
14501600-003	Resistor Assembly PPK, End of Line Resistor, 1.91K Ohms Single Zone Fire Alarm Panels	—
14501600-008	Resistor Assembly PPK, End of Line Resistor, 1.91K Ohms Single Zone Fire Alarm Panels	—
14502286-003	Plate for SC 806	SC806
14502412-005	Lightning Suppressor for Lighting Products	—
14502412-006	Lightning Suppressor for Lighting Products	—
14502412-009	Lightning Suppressor for Lighting Products	—
14502412-010	Lightning Suppressor for Lighting Products	—
14502412-011	Lightning Suppressor for Lighting Products	—
14502412-012	Lightning Suppressor for Lighting Products	—
14502412-014	Lightning Suppressor for Lighting Products	—
14505159-001	Tamper Switch for Cabinet	—
14505393-001	Isolation Transformer, 24V / 50-60 Hz	—
14505928-001	Lock & Key for Cabinet	—
14506587-004	Base for TC804, TC805 Smoke Detector	—
14506635-001	Rough-in Ring, for Half-sized (18 in. x 18 in.) Standard Cabinet (19 in. X 24 in. X 9 in.).	—
14506635-002	Rough-in Ring for Full-sized (36 in. x 36 in.) Standard Cabinet (38 in. X 24 in. X 9 in.).	—
14506636-001	Door with Lock for Half-sized (18 in. x 18 in.) Standard Cabinet.	—
14506636-002	Door with Lock for Full-sized (36 in. x 36 in.) Standard Cabinet.	—
15753205-001	Nameplate, Material: 005 aluminum foil with foam relief liner .020 thick vendor - 3M #Y9394, Letters to be matte aluminum finish. Letters no to be embossed. Background to be Red.	Pneumatic Universal Cabinet
15753207-004	Back Coverplate for Half-sized (18 in. x 18 in.) Standard Cabinet.	—
20133	Dial	—
301572A/0767	Thermostat Key	—
310418A	Pneumatic External Adjustable Restrictor	—
310543	Seat, Valve, Removable, V5005	—
311680	Plug, Orifice, Rubber, TP, LP Thermostats	—
314963	Spring	—
315559E	Pneumatic "Tee" Restrictor	—
316134B	PP901A & B Diaphragm Repair Kit	PP901A,B
316203A	Pressure Regulator Valve Assembly, PP901A & PP901B, PP902A,B.	—
802550	Toggle Switch	—

Product Number	Description	
AK3052W1C	Pneumatic Tubing, Polyethylene Flame Retardant Plastic (5/32 in. O.D. x 0.030 in. wall thickness), Carton qty = 3000 ft	
AK3053W1C	Pneumatic Tubing, Polyethylene Flame Retardant Plastic (1/4 in. O.D. x 0.040 in. wall thickness), Black with Colored Markings, without Fittings, Carton qty = 1500 ft	
AK3056C	Pneumatic Tubing, Polyethylene Flame Retardant Plastic (3/8 in. O.D. x 0.062 in. wall thickness), Black with 1 through 2 White Markings, without Fittings, Carton qty = 1000 ft	
AK3061C	Pneumatic Tubing, Polyethylene Flame Retardant Plastic (1/2 in. O.D. x 0.062 in. wall thickness), Black with 1 through 2 White Markings, without Fittings, Carton qty = 500 ft	
AK3071A	3/8 in. White Stripes	
AK3071B	3/8 in. Red Stripes	
AK3071D	3/8 in. Yellow Stripes	
AK3071G	3/8 in. Violet Stripes	









Gauges and Accessories

Product Number	Description	
AK3240C	Polyethylene Pneumatic Twin Tubing, includes two 5/32 in. O.D. x 0.030 in. Wall Thickness Tubings, Black with Joining Web without Fittings, Carton qty = 1000 ft	
AK3241C	Polyethylene Pneumatic Twin Tubing, includes two 1/4 in. O.D. x 0.040 in. Wall Thickness Tubings, Flame Retardant, Black with Joining Web without Fittings, Carton qty = 5000 ft	
AK3470B	Condensate Trap, 1/2 in., for 1 h.p. or larger compressors	
AK3470C	Condensate Trap, 3/8 in., for 3/4 h.p. or smaller compressors	
AK3485D	Installation Material	
AK3486	Coalescing In-line Pneumatic Filter Kit includes Two Filters with integral barbed fitting for individual devices	
AK3980	Fittings	
AK3997	Free Standing Mounting Kit for one General Purpose Cabinet	
ARR262	Miniature Pressure Regulator (0-125 psi Range), no gauge	
ARR262-S31	Miniature Pressure Regulator (0-125 psi Range), includes 0-160 psi gauge	
ARR262-S32	Miniature Pressure Regulator (0-60 psi Range), includes 0-60 psi gauge	
ARR262-S34	Arrow PRV 0-60	
ARR262I	Miniature Pressure Regulator (0-20 psi Range), no gauge	
ARR262L	Arrow PRV No Gag	
ARRBK1611	Arrow PRV	
CCT1421	1/4 in. Brass Compression Union	
CCT1435T	Pneumatic Fitting - 1/4 in. x 1/8 in. NPT Brass Compression Adapter to NPT,	
CCT1529	Pneumatic Fitting - 1/4 in. Brass Compression Tee,	
CCT1531	Pneumatic Fitting - 3/8 in. Brass Compression Tee,	
CCT1532	Pneumatic Fitting - 1/2 in. Brass Compression Tee,	
CCT1571	Pneumatic Fitting - 1/4 in. Plastic Ferrule (white) for use with plastic tubing and standard compression fittings,	
CCT1572	Pneumatic Fitting - 3/8 in. Plastic Ferrule (white) for use with plastic tubing and standard compression fittings,	
CCT1573	Pneumatic Fitting - 1/2 in. Plastic Ferrule (white) for use with plastic tubing and standard compression fittings,	
CCT1575	Pneumatic Fitting - 1/4 in. Brass Insert for Plastic Tubing,	
CCT1576	Pneumatic Fitting - 3/8 in. Brass Insert for Plastic Tubing,	
CCT1577	Pneumatic Fitting - 1/2 in. Brass Insert for Plastic Tubing,	

Gauges and Accessories

Product Number	Description	
CCT1589B	Pneumatic Fitting - 1/4 in.x1/8 in. FPT 90 Barbed Female Street Ells,	
CCT1590BT	Pneumatic Fitting - 1/4 in. Barbed x 1/8 in. NPT Male Adapter, Taped,	
CCT1594B	Pneumatic Fitting - 1/4 in. Barbed x 1/8 in. FPT Female Adapter,	
CCT1595BT	Pneumatic Fitting - 1/4 in. barbed x 1/8 in. NPT 90 Barbed Male Street Ells,	
CCT1598B	Pneumatic Fitting - 3/8 in. barbed x 3/8 in. barbed 90 Elbow	
CCT1599BT	Pneumatic Fitting - combination 5/32 in. and 1/4 in. Barbed x 1/8 in. NPT Male Adapter, reducing,	
CCT1602	Pneumatic Fitting - In-line gauge Tee (5/32 in. barbed x 5/32 in. barbed x 1/8 in. FPT),	
CCT1606B	Pneumatic Fitting - 5/32 in. barbed x 1/4 in. barbed (brass) plastic tubing coupling, reducing,	
CCT1607B	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. barbed (brass) plastic tubing coupling,	
CCT1608B	Pneumatic Fitting - 3/8 in. barbed x 3/8 in. barbed (brass) plastic tubing coupling,	
CCT1610B	Pneumatic Fitting - 3/8 in. barbed x 1/4 in. barbed (brass) plastic tubing coupling,	
CCT1611B	Pneumatic Fitting - 1/2 in. barbed x 3/8 in. barbed (brass) plastic tubing coupling,	
CCT1612B	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. barbed x 1/4 in. barbed (brass) Straight Tee,	
CCT1613B	Pneumatic Fitting - 3/8 in. barbed x 3/8 in. barbed x 3/8 in. barbed (brass) Straight Tee,	
CCT1614B	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. barbed x 1/8 in. FPT In-line gauge Tee,	
CCT1615B	Pneumatic Fitting - 3/8 in. barbed x 3/8 in. barbed x 1/4 in. barbed Reducing Tee,	
CCT1616B	Pneumatic Fitting - 1/2 in. barbed x 1/2 in. barbed x 1/4 in. barbed Reducing Tee,	









Gauges and Accessories

Product Number	Description	
CCT1617B	Pneumatic Fitting - 1/2 in. barbed x 1/2 in. barbed (brass) plastic tubing coupling,	
CCT1618B	Pneumatic Fitting - 1/2 in. barbed x 1/2 in. barbed x 3/8 in. barbed Reducing Tee,	
CCT1619B	Pneumatic Fitting - Bulkhead Barb, 1/4 in. barbed x 1/4 in. Compression Nuts (for panels 5/16 in. thick),	
CCT1620B	Pneumatic Fitting - 1/2 in. barbed x 1/2 in. barbed x 1/2 in. barbed (brass) Straight Tee,	
CCT1622	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. barbed x 1/8 in. FPT In-line gauge Tee with mounting tabs,	
CCT1623	Pneumatic Fitting - 1/4 in. Spring Clamp for Pneumatic Tubing,	
CCT1628B	Pneumatic Fitting - 5/32 in. barbed x 5/32 in. barbed (brass) plastic tubing coupling,	
CCT1629B	Pneumatic Fitting - 1/2 in. barbed x 1/4 in. barbed (brass) plastic tubing coupling,	
CCT1630B	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. barbed x 5/32 in. barbed Reducing Tee,	
CCT1631B	Pneumatic Fitting - 3/8 in. barbed x 3/8 in. barbed x 5/32 in. barbed Reducing Tee,	
CCT1633BT	Pneumatic Fitting - 1/4 in. Barbed x 1/4 in. NPT Male Adapter,	
CCT1635B	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. Compression Adapter,	
CCT1637B	Pneumatic Fitting - 5/32 in. barbed x 5/32 in. barbed x 5/32 in. barbed (brass) Straight Tee,	
CCT1640	Pneumatic Fitting - 1/4 in. Tubing Plug,	




Gauges and Accessories

Product Number	Description	
CCT1641	Pneumatic Fitting - 5/32 in. barbed x 5/32 in. Brass barbed 90 Elbow,	
CCT1642	Pneumatic Fitting - 1/4 in. barbed x 1/4 in. barbed 90 Elbow,	
CCT1643	Pneumatic Fitting - 1/4 in. barbed x 5/32 in. barbed 90 Elbow	
CCT1650	90 degree brass elbow	
CCT1692T	Pneumatic Fitting - 1/4 in. NPT x 1/8 in. FPT (brass) Pipe Bushing Taped,	
CCT1694T	Pneumatic Fitting - 3/8 in. NPT x 1/4 in. FPT Brass Reducing Pipe Bushing, Taped,	
CCT1696T	Pneumatic Fitting - 1/2 in. NPT x 1/4 in. FPT Brass Reducing Pipe Bushing, Taped,	
CCT1801	Pneumatic Fitting - Rubber Cap for 1/4 in. O.D. Pneumatic Tubing,	
CCT1802	Pneumatic Fitting - Rubber Grommet for 1/4 in. hole used to install capillary in duct	
CCT1807A	Plastic Cap for 3/8 in. Tubing.	
CCT1809	Pneumatic Fitting - Plastic Cap for 1/2 in. O.D. Pneumatic Tubing,	
CCT1815	Pneumatic Fitting - Aluminum Barb Plug for 5/32 in. x 5/32 in. O.D. Pneumatic Tubing (no air passage),	
CCT1820	Plastic Bushing for 1/2 in. EMP or K.O.	
CCT2083T	Pneumatic Fitting - Tank Valve with CCT2084 Cap, 1/8 in. NPT,	
CCT2085	Pneumatic Fitting - Gauge Adapter fits any standard 1/8 in. NPT gauge,	
CCT2090A	Air Check Diode Valve 1/4 in. O.D. Brass, 1.2 SCFM.	
CCT2091	Pneumatic Fitting - Air Check Diode Valve FPT for 1/4 in. O.D. Pneumatic Tubing (4.4 scfm)	
CCT2092	Pneumatic Fitting - Air Check Diode Valve FPT for 3/8 in. O.D. Pneumatic Tubing (7.5 scfm)	
CCT2093	Pneumatic Fitting - Air Check Diode Valve FPT for 1/2 in. O.D. Pneumatic Tubing (12.7 scfm)	
CCT2127B	Pneumatic Fittings - 1/4 in. barbed x 1/4 in. barbed Pneumatic Needle Valve,	



Gauges and Accessories

Product Number	Description	
CCT2564	Pneumatic Fittings - Plated Single Straps for 1/4 in. O.D. Copper Tubing,	
CCT2565	Pneumatic Fittings - Plated Single Straps for 3/8 in. O.D. Copper Tubing,	
CCT2566	Pneumatic Fittings - Plated Single Straps for 1/2 in. O.D. Copper Tubing,	
CCT2626	Pneumatic Fittings - Copper Gang Straps (6 in. wide) for 1/4 in. or 3/8 in. O.D. Copper Tubing,	
CCT2627	Pneumatic Fittings - Copper Gang Straps (36 in. wide) for 1/4 in. or 3/8 in. O.D. Copper Tubing,	
CCT2628	Pneumatic Fittings - Zinc-plated Steel Universal Gang Straps (24 in. wide) for 1/8 in. through 3/4 in. O.D. Copper Tubing,	
CCT2630	Pneumatic Fittings - Aluminum Universal Gang Straps (24 in. wide) for 1/8 in. through 3/4 in. O.D. Copper Tubing,	
CCT2760	Pneumatic Fittings - Adhesive Straps (1 in. wide) for 1/4 in. O.D. Tubing,	
CCT2762	Pneumatic Fittings - Adhesive Straps (1 in. wide) for 3/8 in. O.D. Tubing,	
CCT720B	Tubing Bender for 1/4 in. O.D. Pneumatic Tubing	
CCT722B	Tubing Bender for 3/8 in. O.D. Pneumatic Tubing	
CCT814	Slide Rule for Calculating Pneumatic Valve and Main Air Sizing	
CCT816A	Calibration Kit	
CCT816B	Sensor Calibration Kit; Obsolete Test Kit, use DSP3356 to replace	
CCT817C	Replacement gauge for the DSP3356 Pneumatic Control Calibration Kit	
CCT819	Proportional Band and Authority Setting Adjustment Tool for all RP920's	
CCT852	Pressure Bulb Assembly	
CCT853	Pneumatic Tubing for Test Equipment, 11/32 in. O.D. x 5/32 in. Latex Tubing (10 ft lengths)	
CCT947	Valve Seat Removal Wrench, 2 1/8 in., for V5011 and V5013 (2 in. Valves)	
CCT948	Valve Seat Removal Wrench, 2 5/8 in. for V5011 and V5013 (2-1/2 in. Valves)	
CCT949	Valve Seat Removal Wrench, 3 1/8 in. for V5011 and V5013 (3 in. Valves)	
CCT950	Plastic Tube Holder	

Gauges and Accessories

Product Number	Description	
CCT951	Plastic Tube Fitting Push,.	
CCT970	Thermometer Calibration Tool for Pneumatic Thermostats (TP970, TP971, TP972, TP973, TP9600 series). NOTE: The thermometer on thermostats made after 1988 may also be adjusted using a 1/8 in. allen wrench.	
DSP3356	Calibration Training Kit	
HKN03708008	Separator Drain. Assembly with 16 oz. Metal Bowl (for HKN8015)	
HKN03708304	Separator Drain. Assembly with 16 oz. Metal Bowl (for HKN8005, HKN8010, & HKN8210)	
HKN05417007	Drain Snap-Trap #05.4170-07	
HKN07132	Filter Cartridge for HKN13023 Oil Removal Filter	
HKN07313	Replacement Filter Cartridge for 310 - Hankison International Part No.0731-3	
HKN07341	Filter Sleeve Kit (for HKN8005, HKN8010 & HKN8210)	
HKN07342	Filter Sleeve Kit (for HKN8015, HKN8025 & HKN8035)	
HKN07444101	Separator/Drain. Cartridge (for HKN8005, HKN8010 & HKN8210)	
HKN17012	Bypass Valve Kit, 15 scfm	
HKN44604363	Filter Element, 40 microns with gaskets (for HKN8010, HKN8210, HKN8015, HKN8025 & HKN8210)	
HKN44604364	Filter Element, 40 microns with gaskets (for HKN8045, HKN8055, HKN8070 & HKN80100)	
HKN59301891	High Temperature Sensor, thermo-disc (for HKN8005, HKN8010, HKN8015, HKN8025 & HKN8210)	
HKN61052391	Fan Motor (for HKN8010, HKN8210, HKN8015, HKN8025 & HKN8035, 115VAC/1phase/60Hertz Models only)	
HKN63504548	Dual Light Assembly (for HKN8010, HKN8210, HKN8015, HKN8025 & HKN8035, 115VAC/1phase/60Hertz Models only)	
HKN8015	Compressed Air Dryer, (includes refrigerated air dryer, manual bypass valve, coalescing filter, regulator, operating status light and gauges. 15 scfm @ 80 PSI, 115VAC/1phase/60Hertz	
HKNRDMK1	Maintenance Kit, Hankison Part No.RDMK1	

Gauges and Accessories

Product Number	Description	
MJK100	Pneumatic Fittings Kit - Includes an assortment of fittings most often required for replacement or repair of pneumatic devices.	
MQP800	Pneumatic Calibration Kit with two 0-30 psi gauges	
P246A1009	Static Pressure Regulator	